

DECLARATION OF PERFORMANCE


No. 858-NeutraPass-002-en
according to Regulation (EU) No 305/2011

1. *Unique identification code of the product-type:*
Separator system for light liquids class I with combined sludge trap and an upstream by-pass device – NeutraPass –
2. *Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*
Separator system for light liquids class I with preceded by-pass device – NeutraPass – according to annex List of types
3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*
Separate light liquids from wastewater to protect sewerage systems and surface water.
4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*
Mall GmbH
Hüfinger Strasse 39-45
78166 Donaueschingen
Germany
5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*
Not relevant
6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*
System 4
7. *Name and identification number of the notified body, if relevant:*
Not relevant
8. *Name and identification number of the Technical Assessment Body, if relevant:*
Not relevant
9. *Declared performance:*

Essential Characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 858-1:2002 + A1:2004
Liquid tightness	Pass	
Effectiveness	Pass	
Load bearing capacity	Pass	
Durability	Pass	

10. *The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9*

Donaueschingen, 12.06.2026



Christoph Schulze Wischeler,
Geschäftsführer Mall GmbH

Donaueschingen, 12.06.2026



Clemens Mauz, Mall GmbH

List of types NeutraPass

to the Declaration of performance No. 858-NeutraPass-002-en

Typi	NS/ Q _{max}	S	ød
ÜSI006/018-1200	6/18	1.200	1.500
ÜSI006/030-1200	6/30	1.200	1.500
ÜSI006/060-1200	6/60	1.200	1.500
ÜSI008/024-1600	8/24	1.600	1.500
ÜSI008/040-1600	8/40	1.600	1.500
ÜSI008/080-1600	8/80	1.600	1.500
ÜSI010/030-2000	10/30	2.000	1.500
ÜSI010/050-2000	10/50	2.000	1.500
ÜSI010/100-2000	10/100	2.000	1.500
ÜSI015/045-3000	15/45	3.000	2.000
ÜSI015/075-3000	15/75	3.000	2.000
ÜSI015/150-3000	15/150	3.000	2.000
ÜSI020/060-4000	20/60	4.000	2.000
ÜSI020/100-4000	20/100	4.000	2.000
ÜSI020/200-4000	20/200	4.000	2.000